



# ONE SYSTEMS

## Crossover Presets

Model 212IM with 218Sub-W

Note: All sub woofer delay settings assume the sub woofer physical placement is on the same vertical plane as the main system. If the sub enclosure is physically behind or in front of the main system then the delay values given must be adjusted accordingly.

Note: All setting below are Post Router. The Pre Router settings are user definable.

	LF	HF
Gain	0dB	-7.0dB
Polarity	Norm	Norm
Eq1 Type	PEQ	PEQ
Level	-4.5dB	-5.0dB
Frequency	648Hz	2669Hz
Bandwidth	0.42Oct	0.375 Oct

Eq2 Type	PEQ	PEQ
Level	+3.0	+8.5dB
Frequency	70Hz	15.5kHz
Bandwidth	0.35Oct	0.667Oct

Eq3 Type	PEQ	PEQ
Level	-2.5dB	-4.0dB
Frequency	204Hz	3886Hz
Bandwidth	0.353 Oct	0.5Oct

## Delay

Pre Crossover	0mSec	0mSec
Post Crossover	1.41mSec	1.1mSec

## Crossover

LPF		
Frequency	1029Hz	OFF
Type	24dB L-R*	
HPF		
Frequency	102Hz	1029Hz
Type	24dB L-R	24dB L-R

## Dynamics

Threshold	+6dBu	+2dBu
Comp Ratio	2:1	3:1
Attack	10.0mSec	2mSec
Release	200mSec	125mSec

\* NOTE: L-R = Linkwitz-Riley

## SUB CHANNEL

Gain	0dB
Polarity	Norm

### Eq1

Type	PEQ
Level	+3.0dB
Frequency	41.7Hz
Bandwidth	0.353 Oct

### Delay

Pre Crossover	0mSec
Post Crossover	0mSec

### Crossover

HPF	
Frequency	35.1Hz
Type	24dB Butterworth

LFP	
Frequency	102Hz
Type	24dB L-R

### Dynamics

Threshold	+6dBu
Comp Ratio	2:1
Attack	10.0mSec
Release	200mSec



**One Systems USA, Inc.** \* 6204 Gardendale Dr. \* Nashville, TN 37215

**One Systems Group Co. Ltd.** \* European Division \* Mittelsmoorer Strasse 12 \* 28879 Grassberg German

**One Systems Global Co., Ltd.** \* 87/114 Modern Town 15<sup>th</sup> Floor \* Sukhumvit 63, Ekkamai Soi 3, Klongtoey, Bangkok, 1010 Thailand