

Model	Coverage	Description	Feet	16.5	33	49.5	66	82.5	99	116	132	149	165	182	198	215	231	248	264	281	297	314	330	347	363	380	396	413	429	446	462	479	495	512	528	545	561	578	594	Throw Distance for 90 dB minimum	
			Meter	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125	130	135	140	145	150	155	160	165	170	175	180		
PLATINUM SERIES																																									
108.HTH	60 x 40 / 105 x 60	8-inch two-way																																							60 ft / 18.28 m
208.HTC	70 x 70	Dual 8-inch two-way coax																																							130 ft / 39.39 m
112.HTH	60 x 40 / 105 x 60	12-inch two-way																																							184 ft / 55.8 m
212.HC	70 x 70	Double 12-inch two-way																																							320 ft / 96.96 m
312.HC	70 x 70	Triple 12-inch vertical array																																							320 ft / 96.96 m
CFA2.HTH	55 x 30	Long-throw system																																						570 ft / 172.7 m	
SILVER SERIES																																									
ONE.SP6	90 x 90	6.5-inch coax																																						57 ft / 17.27 m	
ONE.SP8	90 x 40	8-inch two-way																																							104 ft / 31.51 m
ONE.SP12D	60 x 40	12-inch two way																																							360 ft / 109 m
ONE.SP12T	60 x 40	Hi-Z 12-inch																																							325 ft / 98.5 m
ONE.SL12	60 x 40	12-in two-way																																							165 ft / 50 m
ONE.SL15	60 x 40	15-in two-way																																							233 ft / 78.78 m
SUBWOOFERS																																									
108.HSB	omni	8-inch sub								w/ 2 subs																														37 ft / 11.21 m	
112.HSB	omni	12-inch sub																																							184 ft / 55.8 m
118.HSB	omni	18-inch sub																																							260 ft / 70.6 m
SMALL-FORMAT SYSTEMS																																									
104.HTH	110 x 80	4.5-in two-way																																						18 ft / 5.45 m	
106.HTH	110 x 70	6.5-in two-way																																							30 ft / 9.09 m
108.HTC	70 x 70	8-inch coax																																							59 ft / 17.87 m
104.STH	110 x 80	4.5-in two-way																																							16 ft / 4.84 m
106.STH	110 x 70	6.5-in two-way																																							21 ft / 6.36 m
108.STC	70 x 70	8-inch coax																																							36 ft / 10.9 m

- 90 dB SPL minimum calculated output without consideration of temperature, humidity and wind conditions, rounded to nearest cell
- Speaker mounting height not compensated for
- All stated outputs are for the Lo-Z version of each system, except for the ONE.SP12T, which is Hi-Z only
- Please see the engineering data sheet for more details and precise specifications on each model or visit www.onesystems.com.